



# Dynapro AT-M



### P-Metric

- T -Rated
- U.T.Q.G. 560/A/B
- 45/50/55/60/65/70/75 Series

Developed with innovative tread and sidewall designs, the Dynapro AT-M is an aggressive Premium All-Terrain tire for light trucks, vans and sport utility vehicles. The Dynapro AT-M offers unsurpassed grip, style, and performance both on and off-road.



### Dimension Data

Pattern Code **RF10** (P-METRIC) **SUV/LT**

S-Code	Size	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile
					psi	lbs					
1010842	235/75R15 XL	109T	6.5	6.0-8.0	50	2,028	28.8	9.3	7.3	13.0	721
1008665	P255/65R16	106T	7.5	7.0-9.0	44	2,094	29.1	10.2	7.9	13.0	714
1008666	P225/70R16	103T	6.5	6.0-7.5	44	1,819	28.4	9.0	7.0	13.0	731
1008717	P235/70R16 XL	107T	7.0	6.0-8.0	50	2,149	29.0	9.5	7.3	13.0	716
1012617	P245/70R16 XL	111T	7.0	6.5-8.0	44	2,094	29.5	9.8	7.6	13.0	704
1008669	P255/70R16	109T	7.5	6.5-8.5	44	2,271	30.1	10.2	7.9	13.0	690
1009326	P265/70R16	111T	8.0	7.0-9.0	44	2,403	30.6	10.7	8.2	13.0	679
1008718	P225/75R16 XL	106T	6.0	6.0-7.5	50	2,094	29.3	8.8	7.0	13.0	709
1008719	P235/75R16 XL	109T	6.5	6.0-8.0	50	2,271	29.8	9.3	7.3	13.0	697
1008672	P245/75R16	109T	7.0	6.5-8.0	44	2,271	30.5	9.8	7.6	13.0	681
1008708	P265/75R16	114T	7.5	7.0-9.0	44	2,601	31.7	10.5	8.2	13.0	655
1008720	P235/65R17	103T	7.0	6.5-8.5	44	1,929	29.1	9.5	7.3	13.0	714
1008673	P245/65R17	105T	7.0	7.0-8.5	44	2,028	29.5	9.8	7.6	13.0	704
1008674	P255/65R17	110T	7.5	7.0-9.0	44	2,205	30.1	10.2	7.9	13.0	690
1008675	P265/65R17	110T	8.0	7.5-9.5	44	2,337	30.6	10.7	8.2	13.0	679
1008676	P245/70R17	108T	7.0	6.5-8.0	44	2,205	30.6	9.8	7.6	13.0	679
1008677	P255/70R17	110T	7.5	6.5-8.5	44	2,337	31.1	10.2	7.9	13.0	668
1008678	P265/70R17	113T	8.0	7.0-9.0	44	2,535	31.7	10.7	8.2	13.0	655
1009328	P235/75R17	108T	6.5	6.0-8.0	44	2,205	30.9	9.3	7.3	13.0	672
1009518*	P245/75R17	110T	7.0	6.5-8.0	44	2,337	31.5	9.8	7.6	13.0	659
1009519*	P255/75R17	113T	7.0	6.5-8.5	44	2,535	32.1	10.0	7.9	13.0	647
1009659*	P255/60R18	107T	7.5	7.0-9.0	44	2,149	30.0	10.2	7.9	13.0	692
1008681*	P265/60R18	109T	8.0	7.5-9.5	44	2,271	30.5	10.7	8.2	13.0	681
1009521*	P265/65R18	112T	8.0	7.5-9.5	44	2,469	31.5	10.7	8.2	13.0	659
1009329*	P275/65R18	114T	8.0	7.5-9.5	44	2,601	32.1	11.0	8.6	13.0	647
1009520*	P255/70R18	112T	7.5	6.5-8.5	44	2,601	32.1	10.2	7.9	13.0	647
1009330*	P265/70R18	114T	8.0	7.0-9.0	44	2,601	32.6	10.7	8.2	13.0	637
1009331*	305/50R20 XL	120T	9.5	8.5-11.0	50	3,086	32.0	12.4	9.5	12.5	648
1009332*	275/55R20 XL	117T	8.5	7.5-9.5	50	2,833	31.9	11.2	8.6	12.5	651
1009333*	P275/60R20	114T	8.0	7.5-9.5	44	2,601	33.0	11.0	8.6	12.5	630
1009334*	305/45R22 XL	118T	10.0	9.5-11.5	50	2,910	32.8	11.9	9.5	12.5	633

\*BSW : Black Sidewall  
Technical data subject to change without prior notice.



# Dynapro AT-M



### LT-Metric

- R & S-Rated

Developed with innovative tread and sidewall designs, the Dynapro AT-M is an aggressive Premium All-Terrain tire for light trucks, vans and sport utility vehicles. The Dynapro AT-M offers unsurpassed grip, style, and performance both on and off-road.

### Dimension Data

Pattern Code **RF10** (LT-Metric) *SUV/LT*

S-Code	Size	Ply Rating	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile
						psi	lbs					
2001372	LT235/75R15	6	104/101R	6.5	6.0~7.0	S 50 D 50	1,985 1,820	28.9	9.3	7.1	16.5	716
2001373	LT265/70R16	8	110/107R	8.0	7.0 - 8.5	S 50 D 50	2335 2150	30.6	10.7	8.0	16.5	674
2001403	LT305/70R16	10	124/121R	9.0	8.0 - 9.5	S 65 D 65	3,525 3,195	32.8	12.3	9.3	16.5	633
2001929*	LT225/75R16	10	115/112S	6.0	6.0 - 7.0	S 80 D 80	2,680 2,470	29.3	8.8	6.9	16.0	705
2001376	LT245/75R16	10	120/116S	7.0	6.5 - 8.0	S 80 D 80	3,042 2,778	30.5	9.8	7.2	16.5	678
2001312*	LT265/75R16	10	123/120R	7.5	7.0 - 8.0	S 80 D 80	3,415 3,085	31.7	10.5	8.1	16.5	652
2001378	LT285/75R16	10	127/124R	8.0	7.5 ~ 9.0	S 80 D 80	3,805 3,460	32.8	11.4	8.6	16.5	633
2001404	LT315/75R16	8	121R	8.5	8.0 - 10.0	S 50 -	3,195 -	34.6	12.4	9.6	16.5	601
2020031*	LT215/85R16	10	115/112R	6.0	5.5 - 7.0	S 80 D 80	2,680 2,470	30.4	8.5	6.5	16.0	680
2001150*	LT235/85R16	10	120/116R	6.5	6.0 - 7.5	S 80 D 80	3,042 2,778	31.7	9.3	7.0	16.5	651
2001382	LT245/70R17	10	119/116R	7.0	6.5 - 8.0	S 80 D 80	3,000 2,775	30.6	9.8	7.4	16.5	680
2001383	LT265/70R17	10	121/118S	8.0	7.0 - 8.5	S 80 D 80	3,195 2,910	31.7	10.6	8.0	16.0	656
2001819	LT275/70R17	10	121/118R	8	7.0 - 8.5	S 80 D 80	3,195 2,910	32.2	11	8.4	15.9	645
2001405	LT285/70R17	10	121/118S	8.5	7.5 - 9.5	S 80 D 80	3,195 2,910	32.8	11.6	8.7	16.5	634
2001588*	LT295/70R17	10	121/118R	8.5	7.5 - 10.0	S 80 D 80	3,195 2,910	33.3	11.7	9.0	16.5	624
2001402	LT315/70R17	8	121/118R	9.5	8.5 - 10.0	S 50 D 50	3,195 2,910	34.4	12.4	9.6	16.5	604
2001386	LT245/75R17	10	121/118S	7.0	6.5 - 7.5	S 80 D 80	3,195 2,910	31.5	9.8	7.4	16.0	660
2020029*	LT235/80R17	10	120/117R	6.5	6.0 - 7.5	S 80 D 80	3,085 2,835	31.8	9.3	7.1	16.5	653
2001427*	LT325/60R18	10	124/121S	9.5	9.0 - 12.0	S 65 D 65	3,525 3,195	33.3	13.0	9.8	16.0	623
2002012	LT285/65R18	10	125/122S	8.5	8.0-10.0	S 80 D 80	3,415 3,085	32.1	11.0	8.3	16.5	647
2002012*	LT285/65R18	10	125/122S	8.5	8.0-10.0	S 65 D 65	3,195 2,910	32.6	11.5	8.7	16.0	619
2001428*	LT325/65R18	10	127/124S	9.5	9.0 - 12.0	S 65 D 65	3,860 3,525	34.6	13.0	9.9	16.0	600
2001419*	LT275/70R18	10	125/122S	8.0	7.0-8.5	S 80 D 80	3,640 3,305	33.2	11.0	8.3	16.0	608
2001432*	LT285/55R20	10	117/114S	9.0	8.0 - 10.0	S 65 D 80	2,835 2,600	32.4	11.7	8.7	16.0	642
2001433*	LT305/55R20	10	121/118S	9.5	8.5 - 11.0	S 65 D 65	3,195 2,910	33.2	12.4	9.2	16.0	625
2001429*	LT325/60R20	10	126/123S	9.5	9.0 - 12.0	S 65 D 65	3,750 3,415	35.4	13.0	9.8	16.0	587
2001431*	LT275/65R20	10	126/123S	8.0	7.5 - 9.5	S 80 D 80	3,750 3,415	34.1	11.0	8.3	16.0	636
2001430*	LT325/50R22	10	122S	10.0	9.0 - 12.0	S 65 D 65	3,305 3,085	34.8	13.2	9.8	16.0	575
2001369	30X9.50R15	6	104R	7.5	6.5 - 8.5	S 50 -	1,990 -	29.5	9.4	7.2	16.5	699
2001370	31X10.50R15	6	109R	8.5	7.0 - 9.0	S 50 -	2,250 -	30.5	10.6	8.1	16.5	677
2001371	33x12.50R15	6	108R	10.0	9.0 - 11.0	S 35 -	2,205 -	32.5	12.5	9.6	16.5	635

\*BSW : Black Sidewall  
Technical data subject to change without prior notice.